

# Farmall 45C Series II Compact Tractor

45 hp 4WD compact tractor with 3-range HST and L360 loader on R3 turf tires — built for grounds work, property maintenance, and light agricultural use where surface protection matters. Higher 3-point hitch lift capacity (2,756 lb) than the 40C, bigger loader reach and lift, and the same 6-year extended warranty.

| SPECIFICATION                                | DETAIL                                                  |
|----------------------------------------------|---------------------------------------------------------|
| <b>ENGINE</b>                                |                                                         |
| Engine Configuration                         | 3-Cylinder Turbocharged Diesel – Tier 4B Final          |
| Gross Engine Power                           | 45 hp (33.6 kW)                                         |
| PTO Power – HST                              | 36.0 hp (26.8 kW) @ 540 RPM                             |
| Displacement                                 | 1.9 L (116 cu in)                                       |
| Fuel Injection                               | Common Rail Direct Injection                            |
| Emissions                                    | Tier 4B Final – EGR + DPF (50-hr Regen Interval)        |
| Fuel Tank Capacity                           | 10.5 gal (39.7 L)                                       |
| <b>TRANSMISSION &amp; DRIVETRAIN</b>         |                                                         |
| Transmission Type                            | Hydrostatic (HST) – 3-Range                             |
| Forward / Reverse                            | Infinite (3-Range HST)                                  |
| Drive System                                 | 4WD – Mechanical Front Wheel Drive (MFWD)               |
| Steering                                     | Power Steering – Dedicated Pump                         |
| Differential Lock                            | Rear – Mechanical                                       |
| Brakes                                       | Wet Multi-Disc                                          |
| <b>HYDRAULICS &amp; PTO</b>                  |                                                         |
| Hydraulic Flow Rate – Implement Pump         | 9.8 gpm (37.1 L/min)                                    |
| Hydraulic System                             | Open Center – Dual Gear Pump                            |
| 3-Point Hitch Category                       | Category I                                              |
| 3-Point Hitch Lift Capacity – 24" Behind Pin | 2,756 lb (1,250 kg)                                     |
| 3-Point Lower Links                          | Telescoping Stabilizers / Flex-End Lower Links          |
| Drawbar                                      | Extendable – 2-Position                                 |
| Rear PTO Speed                               | 540 RPM – Independent Electro-Hydraulic                 |
| Mid PTO Speed                                | 2,000 RPM – Fitted                                      |
| Rear Remote Valves                           | 2 – Fitted                                              |
| <b>OPERATOR CAB</b>                          |                                                         |
| Cab Type                                     | Factory Enclosed Cab – ROPS Certified                   |
| Visibility                                   | Sloped Hood – Clear Forward Sight Lines to Front Wheels |

|                                        |                                                     |
|----------------------------------------|-----------------------------------------------------|
| <b>Controls</b>                        | Hand & Foot Throttle – Color-Coded Hydraulic Levers |
| <b>Seat</b>                            | Adjustable Suspension Seat                          |
| <b>DIMENSIONS &amp; WEIGHT</b>         |                                                     |
| <b>Operating Weight (with Loader)</b>  | 6,300 lb (2,858 kg)                                 |
| <b>Wheelbase</b>                       | 73.2 in (1,860 mm)                                  |
| <b>Front Tires</b>                     | 28x8.50-15, 6PR (R3 Turf)                           |
| <b>Rear Tires</b>                      | 41x14.00-20, 4PR (R3 Turf)                          |
| <b>FRONT END LOADER – L360</b>         |                                                     |
| <b>Loader Model</b>                    | Case IH L360 Front End Loader                       |
| <b>Loader Serial</b>                   | YRM362108                                           |
| <b>Max Lift Capacity – Full Height</b> | 1,830 lb (830 kg)                                   |
| <b>Boom Breakout Force</b>             | 3,114 lb (1,412 kg)                                 |
| <b>Max Dump Height</b>                 | 112 in (2,845 mm)                                   |
| <b>Coupler</b>                         | Skid Steer Quick-Attach (SSQA)                      |
| <b>UNIT INFORMATION</b>                |                                                     |
| <b>Model</b>                           | Case IH Farmall 45C Series II – 4WD Compact Tractor |
| <b>Year / Production Date</b>          | 2024 (Feb 22, 2024)                                 |
| <b>PIN / Serial Number</b>             | LSMF45CCEP0020124                                   |
| <b>Loader Serial</b>                   | YRM362108                                           |
| <b>Condition</b>                       | New                                                 |
| <b>Location</b>                        | Florenceville-Bristol, NB                           |
| <b>INCLUDED OPTIONS &amp; FEATURES</b> |                                                     |
| <b>Transmission</b>                    | Hydrostatic (HST) – 3-Range                         |
| <b>Cab</b>                             | Factory Enclosed – ROPS Certified                   |
| <b>Drive</b>                           | 4WD – MFWD                                          |
| <b>Front End Loader</b>                | L360 – Skid Steer Quick Attach (SSQA)               |
| <b>Mid PTO Kit</b>                     | Yes – 2,000 RPM                                     |
| <b>Rear Remote Valves</b>              | 2 – Fitted                                          |
| <b>Front Tires</b>                     | 28x8.50-15 R3 Turf (Lawn-Friendly)                  |
| <b>Rear Tires</b>                      | 41x14.00-20 R3 Turf (Lawn-Friendly)                 |
| <b>Warranty</b>                        | 6-Year Extended Warranty                            |
| <b>Operator's Manual</b>               | English                                             |

### Interested in this unit?

Contact our sales team and a representative will be in touch with you shortly.

 Toll Free: 1-888-461-6070

 [countytractorsnb.com](http://countytractorsnb.com) | Florenceville-Bristol, NB

County Tractors & Machinery Ltd. — Authorized Case IH Dealer