

Farmall 75C Utility Tractor

75 hp 4WD utility tractor — the C-Series step up from the 75A with more engine displacement, intercooled turbo, air suspension seat, Lift-O-Matic Plus hitch, electro-hydraulic 4WD front axle, and factory-matched L620 loader. 3,664 lb three-point hitch capacity, 5,556 lb loader breakout force, and a deluxe enclosed cab built for long days.

SPECIFICATION	DETAIL
ENGINE	
Engine Make / Model	FPT – 4-Cylinder Turbocharged & Intercooled Diesel
Gross Engine Power	75 hp (56 kW)
PTO Power (Claimed)	62 hp (46.2 kW) @ 540 RPM
Displacement	3.4 L (208 cu in)
Fuel Injection	Common Rail High-Pressure Electronic Direct Injection
Aspiration	Turbocharged & Intercooled
Emissions	Tier 4A
Fuel Tank Capacity	18.5 gal (70 L)
Engine Exhaust	A-Pillar with Guard
TRANSMISSION & DRIVETRAIN	
Transmission Type	12x12 Power Shuttle – Clutchless Direction Change
Forward / Reverse Speeds	12 Forward / 12 Reverse
Max Ground Speed	25 mph (40 km/h)
Drive System	4WD – Electro-Hydraulic Limited Slip Front Axle
Park Lock	Hand Brake – Fitted
Steering	Power Steering
Brakes	Wet Disc
HYDRAULICS & PTO	
Implement Hydraulic Pump Flow	12.5 gpm (47.3 L/min)
Steering Hydraulic Pump Flow	7.3 gpm (27.6 L/min)
Hydraulic System	Open Center – Separate Steering & Implement Reservoirs
3-Point Hitch Category	Category II / I
3-Point Hitch Lift Capacity – 24" Behind Pin	3,664 lb (1,662 kg)
3-Point Hitch Lift Capacity – At Lift Pin	4,832 lb (2,192 kg)
3-Point Hitch	Lift-O-Matic Plus – One-Touch Raise/Lower
3-Point Hitch Control	External Mechanical Ground Control – Fitted
3-Point Lower Links	Flex Ends TLSPC Stabilizers – Telescoping
Rear PTO Speed	540 RPM – Fully Independent

Mid-Mount Valve & Joystick	2-Function New Trim Joystick – Fitted
Rear Remote Valves	2 Remotes – 4 Couplers – Fitted
OPERATOR CAB	
Cab Type	Deluxe Enclosed Cab – High-Vis Panel
Seat	Deluxe Fabric Seat – Air Suspension
Radio	Bluetooth Radio – Fitted
Instructor Seat	Yes – Fitted
Work Lamps	2 Front / 2 Rear – Fitted
Road Lights	Head Beam Lights – Fitted
Rear Fenders	30-34" – Fitted
DIMENSIONS & WEIGHT	
Operating Weight (with Loader)	6,239 lb (2,830 kg)
Wheelbase – 4WD	87.4 in (2,220 mm)
Front Tires	11.2x24 R1 Agricultural
Rear Tires	16.9x30, 6PR R1 Agricultural
Rear Ballast	4 x 110 lb Rear Wheel Weights – Fitted
Front Tow Hook	Yes – Fitted
FRONT END LOADER – L620	
Loader Model	Case IH L620 – Non-Self-Level (EU Style)
Compatible Tractors	Farmall Utility 65C–120C – Factory Matched
Max Lift Capacity – 31.5" from Pivot (NSL)	2,478 lb (1,124 kg)
Max Lift Capacity – At Pivot Point (NSL)	3,466 lb (1,572 kg)
Boom Breakout Force – Pivot Point (NSL)	5,556 lb (2,520 kg)
Boom Breakout Force – 31.5" from Pivot (NSL)	3,739 lb (1,696 kg)
Max Height – To Bucket Pivot	~142 in (3,600 mm)
Max Dump Angle	58°
Bucket Width	84 in (2,134 mm)
Raise Time to Full Height	5.3 seconds
UNIT INFORMATION	
Model	Case IH Farmall 75C – 4WD Utility Tractor with L620 Loader
Year / Production Date	2026 (Feb 14, 2026)
PIN / Serial Number	ELRFC075VTAP00073
Condition	New
Location	Confirm: Florenceville-Bristol or Salisbury, NB

INCLUDED OPTIONS & FEATURES	
Transmission	12x12 Power Shuttle – Clutchless Direction Change
Cab	Deluxe Enclosed – Air Suspension Seat, Bluetooth Radio, Instructor Seat
Drive	4WD – Electro-Hydraulic Limited Slip Front Axle
Front End Loader	L620 – Non-Self-Level, EU Quick-Attach
Bucket	84" – Fitted
3-Point Hitch	Lift-O-Matic Plus – One-Touch Control
Mid-Mount Valves	2-Function New Trim Joystick – Fitted
Rear Remote Valves	2 Remotes / 4 Couplers – Fitted
Rear Ballast	4 x 110 lb Rear Wheel Weights
Front Tow Hook	Yes
Rear Fenders	30-34"
Work / Road Lights	2F/2R Work Lamps + Head Beam Road Lights
Operator's Manual	English

Interested in this unit?

Contact our sales team and a representative will be in touch with you shortly.

 Toll Free: 1-888-461-6070

 countytractorsnb.com | Florenceville-Bristol / Salisbury, NB