

Workmaster 25S Subcompact Tractor – Cab & Loader

4WD subcompact tractor with enclosed cab and 100LC quick-attach loader — work year-round in comfort. Hydrostatic transmission, R3 turf tires, Category 1 three-point hitch, and electro-hydraulic PTO. The enclosed cab adds heat and weather protection without sacrificing visibility.

SPECIFICATION	DETAIL
ENGINE	
Engine Make / Model	Yanmar 3TNV80F – 3-Cylinder Diesel
Gross Engine Power	24.7 hp (18.4 kW)
PTO Power	17.2 hp (12.8 kW)
Displacement	77.3 cu in (1.27 L)
Aspiration	Naturally Aspirated
Cooling	Liquid Cooled
Emissions	Tier 4 Final
Fuel Tank Capacity	5.6 gal (21.2 L)
TRANSMISSION & DRIVETRAIN	
Transmission Type	Hydrostatic (HST) – 2-Range
Forward / Reverse Speeds	Infinite (2-Range HST)
Max Forward Speed	9.1 mph (14.6 km/h)
Max Reverse Speed	5.5 mph (8.8 km/h)
Drive System	4WD – Mechanical Front Wheel Drive (MFWD)
Steering	Power Steering
Brakes	Wet Multi-Disc
HYDRAULICS & PTO	
Hydraulic System	Open Center – Gear Pump
Hydraulic Flow Rate	4.6 gpm (17.4 L/min)
3-Point Hitch Lift Capacity	1,190 lb (540 kg) at Ball Ends
3-Point Hitch Category	Category 1
Rear PTO Speed	540 RPM
Mid PTO Speed	2,500 RPM
PTO Clutch	Electro-Hydraulic
OPERATOR CAB	
Cab Type	WM25S Subcompact Enclosed Cab
Cab Serial	MT1CAN0
Entry	2-Door
Visibility	4-Post Design – Full Glass Surround
Heat	Yes

Air Conditioning	No
DIMENSIONS & WEIGHT	
Operating Weight (Tractor Only)	2,338 lb (1,060 kg)
Wheelbase	56.1 in (1,424 mm)
Ground Clearance	11.0 in (279 mm)
Front Tires	18x8.50-10 (R3 Turf)
Rear Tires	26x12.00-12 (R3 Turf)
FRONT END LOADER – 100LC	
Loader Model	New Holland 100LC – Quick Attach
Loader Serial	240415040
Lift Capacity – Full Height	925 lb (420 kg)
Bucket Breakout Force	2,204 lb (1,000 kg)
Max Dump Height	73 in (1,854 mm)
Bucket	Standard Bucket
UNIT INFORMATION	
Model	New Holland Workmaster 25S – 4WD Subcompact Tractor with Cab
Year / Production Date	MY2024 (May 9, 2024)
PIN / Serial Number	LSM0W25SPR0022546
Loader Serial	240415040
Cab Serial	MT1CAN0
Condition	New
Location	Salisbury, NB
INCLUDED OPTIONS & FEATURES	
Operator Enclosure	WM25S Subcompact Enclosed Cab – 2-Door with Heat
Drive	4WD – MFWD
Front End Loader	100LC – Quick Attach
Front Tires	18x8.50-10 (R3 Turf – Lawn-Friendly)
Rear Tires	26x12.00-12 (R3 Turf – Lawn-Friendly)
Operator's Manual	English

Interested in this unit?

Contact our sales team and a representative will be in touch with you shortly.

 Toll Free: 1-888-461-6070

 countytractorsnb.com | Salisbury, NB