

C314 Mini Track Loader

Stand-on mini track loader built for landscaping, residential construction, and tight-access jobsites. Radial lift geometry, 29-attachment compatibility, and a narrow frame that goes where wheeled machines can't.

SPECIFICATION	DETAIL
ENGINE	
Engine Make	Kubota Diesel
Engine Power	24 hp (17.9 kW)
Emissions Compliance	Stage V
Rated Speed	2,600 RPM
PERFORMANCE	
Rated Operating Capacity – Narrow Track (35% TL)	992 lb (450 kg)
Rated Operating Capacity – Wide Track (35% TL)	1,102 lb (500 kg)
Tipping Load – Narrow Track	2,833 lb (1,285 kg)
Tipping Load – Wide Track	3,148 lb (1,428 kg)
Max Travel Speed	4.7 mph (7.6 km/h)
Transmission Type	Hydrostatic
HYDRAULICS	
Auxiliary Hydraulic Flow Rate	15 gpm (56.8 L/min)
Attachment Interface	Common Industry Interface – 14-pin electric multifunction control
LIFT & REACH	
Lift Type	Radial Lift
Hinge Pin Height	86.7 in (2,202 mm)
Dump Height – Standard Bucket	61.0 in (1,549 mm)
Max Reach at Dump Height	20.1 in (511 mm)
Max Rollback at Full Height	90°
Dump Angle	48°
DIMENSIONS	
Machine Width – Narrow Track	35.0 in (889 mm)
Machine Width – Wide Track	40.4 in (1,026 mm)
Overall Height	56.5 in (1,435 mm)
Overall Length – Without Bucket	85.6 in (2,175 mm)
Overall Length – With Standard Bucket	110.1 in (2,797 mm)

Rear Departure Angle	24°
Rear Clearance Circle Radius	53.1 in (1,349 mm)
WEIGHT	
Operating Weight – Narrow Track	3,536 lb (1,604 kg)
Operating Weight – Wide Track	3,783 lb (1,716 kg)
UNIT INFORMATION	
Model	New Holland C314 MTL
Year / Production Date	MY2024 (Feb 15, 2024)
PIN / Serial Number	SMP5N631PZMA00096
Condition	New
Location	Salisbury, NB
INCLUDED OPTIONS & ATTACHMENTS	
Auto Engine Shutoff	Yes
Bio Hydraulic Oil	Yes
Front Electric & Case Drain	Yes
Bucket	42" Bolt-On Cutting Edge
Operator's Manual	English

Interested in this unit?

Contact our sales team and a representative will be in touch with you shortly.

 Toll Free: 1-888-461-6070

 countytractorsnb.com | Salisbury, NB