

# C345 Compact Track Loader

Top-tier large-frame compact track loader with 4,500 lb rated operating capacity and 90 hp FPT engine — the most powerful CTL in the New Holland 300 Series. Super Boom® vertical lift, high flow hydraulics, E-H controls, and 450mm tracks built for demanding construction, agricultural, and industrial applications.

| SPECIFICATION                               | DETAIL                                   |
|---------------------------------------------|------------------------------------------|
| <b>ENGINE</b>                               |                                          |
| Engine Make / Model                         | FPT Industrial – 4-Cylinder Tier 4 Final |
| Gross Power                                 | 90 hp (67 kW)                            |
| Emissions                                   | Tier 4 Final                             |
| Fuel Tank Capacity                          | 20 gal (75.5 L)                          |
| <b>PERFORMANCE</b>                          |                                          |
| Rated Operating Capacity – 50% Tipping Load | 4,500 lb (2,045 kg)                      |
| Rated Operating Capacity – 35% Tipping Load | 3,150 lb (1,432 kg)                      |
| Full Rated Operating Load                   | 9,000 lb (4,091 kg)                      |
| Operating Weight                            | 10,000 lb (4,536 kg)                     |
| Max Travel Speed                            | 8.0 mph (12.9 km/h)                      |
| Transmission                                | Hydrostatic – Dual Range                 |
| <b>LIFT GEOMETRY</b>                        |                                          |
| Lift Type                                   | Super Boom® Vertical Lift                |
| Max Hinge Pin Height                        | 131.6 in (3,343 mm)                      |
| Dump Height – Maximum                       | 104.1 in (2,644 mm)                      |
| Dump Height Reach                           | 31.6 in (802 mm)                         |
| Track on Ground                             | 64.5 in (1,639 mm)                       |
| Ground Clearance                            | 9.6 in (244 mm)                          |
| <b>HYDRAULICS</b>                           |                                          |
| Standard Aux Flow                           | 22.6 gpm (85.5 L/min)                    |
| High Flow Aux (Fitted)                      | 34.2 gpm (129.5 L/min)                   |
| Hydraulic Coupler                           | Hydraulic Coupler – Fitted               |
| Aux Configuration                           | High Flow Auxiliary                      |
| <b>UNDERCARRIAGE</b>                        |                                          |
| Track Type                                  | Steel-Embedded Rubber Tracks             |
| Track Width                                 | 450 mm (17.7 in)                         |
| Undercarriage Type                          | Standard Track                           |

| DIMENSIONS                     |                                                             |
|--------------------------------|-------------------------------------------------------------|
| Overall Height – Cab           | 80.4 in (2,042 mm)                                          |
| Height – To Hinge Pin (Raised) | 131.6 in (3,343 mm)                                         |
| UNIT INFORMATION               |                                                             |
| Model                          | New Holland C345 T4F Compact Track Loader                   |
| Year / Production Date         | MY2026 (Jan 28, 2026)                                       |
| PIN / Serial Number            | JAF0C345CTM473989                                           |
| Condition                      | New                                                         |
| Location                       | Salisbury, NB                                               |
| INCLUDED OPTIONS & FEATURES    |                                                             |
| Cab                            | Enclosed Cab w/ E-H Controls & 8" LCD Display               |
| Front Door                     | Glass Front Door                                            |
| Seat                           | Air Ride Suspension Seat                                    |
| Drive Controls                 | Electro-Hydraulic (E-H)                                     |
| Hydraulic Coupler              | Yes – Hydraulic                                             |
| Hydraulic Aux                  | High Flow Auxiliary                                         |
| Tracks                         | 450 mm (17.7") Steel-Embedded Rubber Tracks                 |
| Bucket                         | 84" Low Profile Extended                                    |
| Cutting Edge                   | 84" Bolt-On                                                 |
| Telematics                     | New Holland FleetForce™ – Connectivity NA + Customer Portal |
| Display                        | 8" LCD Multifunction with Integrated Rear Camera            |
| Operator's Manual              | English                                                     |

### Interested in this unit?

Contact our sales team and a representative will be in touch with you shortly.

 Toll Free: 1-888-461-6070

 [countytractorsnb.com](https://countytractorsnb.com) | Salisbury, NB