

W80C Compact Wheel Loader

High-speed compact wheel loader built for heavy load-and-carry, grading, and agricultural material handling. Z-Bar linkage, SSL-compatible coupler, Nokian snow tires, double aux high flow, and a maintenance-free Tier 4 Final engine — ready for New Brunswick winters.

SPECIFICATION	DETAIL
ENGINE	
Engine Make	FPT Industrial – 4-Cylinder Tier 4 Final
Gross Power	74 hp (55 kW)
Displacement	3.4 L (0.9 gal)
Peak Torque (Gross @ 1,400 RPM)	233 ft-lb (316 Nm)
Emissions	Tier 4 Final – Maintenance-Free (No DPF / No DEF)
Fuel Tank Capacity	23 gal (87 L)
Cold Weather Starting	Block Heater Fitted
PERFORMANCE	
Operating Weight	13,100 lb (5,942 kg)
Tipping Load – ISO Straight (with CWT)	10,031 lb (4,550 kg)
Tipping Load – ISO 40° Turn (with CWT)	8,510 lb (3,860 kg)
Operating Load – ISO (with CWT)	4,006 lb (1,817 kg)
Max Travel Speed (High Speed)	21 mph (33.8 km/h)
Transmission	Hydrostatic – High Speed (Press & Go)
Axles	Limited Slip Differential – Front & Rear
LOADER PERFORMANCE	
Linkage Type	Z-Bar (High Breakout / Load-and-Carry)
Breakout Force	13,927 lbf (6,317 kgF)
Lifting Capacity – Full Height	8,424 lb (3,821 kg)
Lifting Capacity – At Maximum Reach	10,644 lb (4,828 kg)
Lifting Capacity – At Ground	13,746 lb (6,235 kg)
Dump Height	99.3 in (2,521 mm)
Hinge Pin Height	132 in (3,353 mm)
HYDRAULICS	
Standard Aux Flow	22.5 gpm
High Flow Aux (Fitted – Double Aux)	34.3 gpm
Aux Configuration	Double Aux High Flow with Creep

Hydraulic Coupler	SSL Compatible (Skid Steer Style)
Hydraulic Tank Capacity	11 gal (40 L)
Auto Ride Control	Yes – Fitted
DIMENSIONS	
Overall Width (Without Bucket)	73 in (1,860 mm)
Cab Height	106 in (2,680 mm)
Operating Height – Fully Raised	169 in (4,322 mm)
Wheelbase	88 in (2,225 mm)
Tread Width	59 in (1,500 mm)
Ground Clearance – Under Axles	15 in (370 mm)
Angle of Departure	32°
Loader Clearance Circle	335 in (8,596 mm)
Tires	360/80 R20 Nokian Tri 2 Snow
UNIT INFORMATION	
Model	New Holland W80C T4 HS ZB EVO – Compact Wheel Loader
Year / Production Date	MY2025 (Dec 2, 2025)
PIN / Serial Number	FNHW80CHNSHP09090
Condition	New
Location	Salisbury, NB
INCLUDED OPTIONS & FEATURES	
Cab	Deluxe Enclosed Cab
Seat	Air Seat
Rear Camera	Yes
Auto Ride Control	Yes
Tires	360/80 R20 Nokian Tri 2 Snow
Road & Work Lights	LED – 2 Front / 2 Rear
Warning Light	Rotating LED Amber Beacon
Cold Weather Package	Block Heater
Axles	High Speed – Limited Slip Differential (Front & Rear)
Hydraulic Aux	Double Aux High Flow with Creep Control
Hydraulic Coupler	Hydraulic SSL Compatible Coupler
Bucket	1.70 cu yd LM Bucket – SSL Coupler
Cutting Edge	2,100 mm
Telematics	New Holland FleetForce™ Included
Operator's Manual	English

Interested in this unit?

Contact our sales team and a representative will be in touch with you shortly.

 Toll Free: 1-888-461-6070

 countytractorsnb.com | Salisbury, NB

County Tractors & Machinery Ltd. — Authorized New Holland Construction Dealer